# Intellian t80W

### **85cm Marine Stabilized Ku-Band**

Global Satellite TV Antenna System



#### Intellian WorldView™ LNB module

Intellian t80W provides the ultimate convenience to connect you up to thousands of Free TV, Pay TV, Standard Definition, and High Definition programming all over the world with one LNB module which incorporates multi (8) LO frequencies.

#### DVB / DVB-S2 signal reception

The fully stabilized, 3-axis t80W is a 85cm satellite TV antenna system that is exclusively designed to support viewing all Standard Definition (SD) and HD programming broadcast through both DVB and the latest DVB-S2 satellite TV service standards.

#### I Dedicated Management Ethernet Port

The Management Ethernet Port on the front of ACU enables direct and simple network connection between a PC and the ACU. The Management

Port supports DHCP network connection by default, allowing automatic IP configurations and quick access to Intellian's remote management solution, Aptus Web.

#### I Global satellite library

The t80W includes the pre-programmed global satellite library which allows boaters to select the desired satellite while travelling from region to region. Once the satellite is selected the WorldView LNB module will automatically switch to the corresponding local frequency to receive the signal.

#### Rugged construction

Built with Intellian's extremely high vibration and shock standards, the t80W's simplified yet sophisticated mechanical design is capable of withstanding the most severe marine environment and is guaranteed to track and lock onto the satellite signal instantly in all weather conditions.

#### Wireless Connectivity

The built-in Wi-Fi enables the ACU to be wirelessly connected and can be either turned on and off by a switch. Any kind of wireless devices such as PCs, laptops and smartphones can be used to connect to the ACU and monitor, control and change the settings of the system wirelessly.



## Intellian t80W

#### I Technical Specifications

. . .

Physical			
Radome Height	120.5cm / 47.4"		
Radome Diameter	113cm / 44.5"		
Reflector Diameter	85cm / 33.5"		
Weight	82.2Kg / 181.2lbs		
Environmental			
Operating Temp. Range	-25°C to +55°C / -13°F to +131°F		
Storage Temp. Range	-40°C to +80°C / -40°F to +176°F		
Water Ingress	IPX6		
Approvals	CE / FCC		
Warranty	3 year parts and 1 year labor		
Performance			
<b>Reception Frequency</b>	Ku-band (10.7~12.75GHz)		
Polarization	Circular / Linear auto-switchable		
Minimum EIRP	44dBW		
Azimuth Range	680°		
Elevation Range	-15° to +110°		
Ship's Motion	Roll ±25°, Pitch ±15°, Yaw ±8° @ 6 sec period		
Turning Rate	Up to 12°/sec & 5°/sec <sup>2</sup>		
RF Output	Quad Output		
Antenna Control Unit			
Dimensions (WxDxH)	43.1cm x 38cm x 4.4cm / 17" x 15" x 1.7"		
Weight	3.5kg / 7.7lbs		
Display	2 line 40 Character VFD module		
GPS Interface	Built-in (NMEA 0183 GPS)		
Power Requirement	100~240V AC, 50~60Hz, 2A		
Power Consumption	Typ.50W, Max. 100W		
LNB LO Frequencies			
Local Oscillator Frequency	Polarization	Area	
11.250 GHz	Dual Circular	North America, Russia	
10.500 GHz	Dual Circular	Latin America	
10.750 GHz	Single Circular	Korea	
10.750 GHz	Dual Circular	China	
10.678 GHz	Single Circular	Japan	
11.300 GHz	Dual Linear	South East Asia	
10.700 GHz	Dual Linear	Australia	
Universal Low: 9.75 GHz High: 10.6 GHz	Quad Linear	Europe, Middle East, Africa, some Asia countries	

LNB stability: ±25 kHz (Except at Universal 9.75 GHz)

LNB LO frequencies can be extended

LNB LO frequencies are automatically changed according to target satellites

· Polarization can be switched between circular and linear

#### 85cm Marine Stabilized Ku-Band

Global Satellite TV Antenna System

#### Intellian t80W is the world's first marine satellite TV

antenna system that truly works with any Kuband satellite TV service around the globe without requiring LNBs to be swapped out or re-wiring the system when the vessel travels from region to region.

The fully stabilized, 3-axis t80W is a 85cm satellite TV antenna system that is exclusively designed to support viewing all Standard Definition (SD) and HD programming broadcast through both DVB and the latest DVB-S2 satellite TV service standards.

Integrated with the exclusive, patented, groundbreaking WorldView<sup>™</sup> LNB module and Intellian's exclusive preprogrammed Global satellite library, the t80W allows you to tune into any channel on any satellite by simply pushing the button on your remote control. The t80W will automatically switch between circular polarized programming in North, Central and South Americas, and linear polarized programming in Europe, the Middle East, and the Asia Pacific region.

Built with Intellian's extremely high vibration and shock standards, the t80W's simplified yet sophisticated mechanical design is capable of withstanding the most severe marine environment and is guaranteed to track and lock onto the satellite signal instantly in all weather conditions.

#### System Diagram

Antenna Control Un	******
RF1	Receiver 1
RF2	Reciever 2
RF3	Reciever 4
RF4	

\*Recievers are not supplied



Note

Global HQ Innovation Center / Factory Intellian Technologies, Inc T +82 31 379 1000 F +82 31 377 6185 APAC Seoul Office Intellian Technologies, Inc. T +82 2 511 2244 F +82 2 511 2235

Irvine Office Intellian Technologies USA, Inc. T +1 949 727 4498 F +1 949 271 4183 Toll Free +1 888-201-9223

**Americas** 

EMEA Rotterdam Office Intellian B.V. T +31 1 0820 8655 F +31 1 0820 8656 art No. 2016D0-DS0218-V4

©2016 Intellian Technologies, Inc. All rights reserved. Intellian and the Intellian logo are registered trademarks. Worldview, t80W and t-Series are trademarks of Intellian Technologies, Inc. in the U.S. and/or various countries. All other trademarks are the property of their respective owners. Information in this document is subject to change without notice. ISO9001 / ISO14001 Certified Intellian has more worldwide offices. Addresses, phone numbers, and fax numbers are listed on the Intellian Website at intelliantech.com